

### **CROSS-REFERENCE TO RELATED APPLICATIONS**

10

## 15

15

## 20

20

## SUMMARY

Briefly described, the present invention generally is directed to a strainer assembly having flow control apertures that can affect the characteristics of the flow of fluid drawn through the assembly when a negative pressure or suction is applied. The body of the strainer assembly includes a primary opening through which fluid exits the body and a series of flow control apertures through which fluid passes before exiting the body. The flow control apertures can be sized and distributed along the body of the strainer assembly in such a way that the area of a given flow control aperture is greater than the areas of the flow control apertures that are closer to or proximally aligned with the primary opening. Alternatively, the positioning of the flow control apertures may be such that the collective area of flow control apertures in a given area of the body or at a given distance from the primary opening is greater than the collective area of flow control apertures in a similarly sized area of the body that is closer to or proximally aligned with the primary opening.

In one embodiment, the present invention includes a strainer assembly having a strainer body defining an internal chamber and having a primary opening formed therein. The strainer body includes a wall encompassing at least a portion of internal chamber. A series of flow control apertures is formed in the wall and includes at least a first flow control aperture proximate to the primary opening and a second flow control aperture distal to the primary opening. The area of the second flow control aperture is greater than the area of the first flow control aperture. Indeed, when the series includes more than two flow control apertures extending along the body away from the primary opening, the area of each flow control aperture can be greater than the area of those apertures that are closer to or proximal with the primary opening. Also, the flow control apertures can be covered by screen, which can limit the size of

solid matter flowing into the assembly. The body of the strainer assembly can be formed, in part, by one or more flow control plates having flow control apertures formed therein. For instance, the primary opening can be formed in a flow control plate and have a plurality of flow control aperture series radially aligned therewith. A second flow control plate with flow control apertures also can be provided spaced from the first plate and include flow control apertures and a secondary opening through which fluid flows into the body.

In accordance with the present invention, the strainer assembly can include a body with both a primary opening, through which fluid exits the body, and a secondary opening, through which fluid enters the body from another strainer. The body includes a first flow control plate in which the primary opening and a first plurality of flow control apertures is formed. The collective area of flow control apertures of this first plurality of flow control apertures increases distally from the primary opening. In other words, for a given area on the flow control plate, the combined area of the flow control apertures in that given area is greater than the combined area of flow control apertures in another given area of similar dimensions that is located closer to or proximal with the primary opening. The body also includes a second flow control plate connected to the first flow control plate and having a secondary opening and a second plurality of flow control apertures formed therein. Again, the collective area of flow control apertures of this second plurality of flow control apertures increases distally from the secondary opening. A rim can be disposed between the first and second flow control plates and may itself have rim flow control apertures formed therein. One or more screens can extend across the flow control apertures on the flow control plates.

The present invention also is directed to a suction strainer for connection to a suction inlet of a pump. The suction strainer can include a plurality of strainers in flow communication with a

suction inlet of a pump. At least one of the strainers includes a strainer body defining a internal chamber and having a primary opening formed therein through which fluid exits the strainer toward the suction inlet. The wall of the strainer body encompasses at least a portion of the internal chamber and includes a plurality of flow control apertures formed therein. The collective area of flow control apertures increases distally from the primary opening. For any given area, the total area of the flow control apertures in that area is greater than the total area of flow control apertures in an area of similar size that is closer to the primary opening. The plurality of strainers may be sequentially aligned along a flow line leading to the suction inlet. In one embodiment, the flow line leading to the suction inlet is formed in part by the internal chambers of the strainers, which are aligned such that one empties into another toward the suction inlet. Screen may cover one or more of the flow control apertures of the strainers so as to limit the size and amount of solids material passing therethrough. In one particular embodiment, the overall or aggregate area of the flow control apertures in a given strainer is greater than the overall or aggregate area of the flow control apertures in other individual strainers that are closer to or proximally aligned with the suction inlet of the pump. In other words, the aggregate area of flow control apertures in each strainer increases distally from the suction inlet.

These and other aspects of the present invention are set forth in greater detail in the detailed description and the drawings, which are briefly described as follows.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a schematic, side elevational view of a suction strainer encompassing aspects of the present invention.

Fig. 2 is a cutaway view of the section 2 of the suction strainer of Fig. 1 taken along line 2-2.

Fig. 3 is a partial exploded perspective view of the suction strainer of Fig. 1.

5

### **DETAILED DESCRIPTION**

Referring now in greater detail to the drawings, in which like numerals represent like components throughout the several views, Fig. 1 discloses a suction strainer 20 that encompasses aspects of the present invention. The suction strainer 20 includes a plurality of strainer bodies 21  
10 that are in flow communication with the suction inlet 40 of a suction pump and with a fluid, such as water, generally surrounding the suction strainer 20. The suction strainer 20 can be completely or partially submersed in the fluid, which can be, for example, water in a lake, river, or pond, and provide intake surfaces for the suction pump. The suction strainer 20 includes flow control mechanisms, such as flow control plates 30 and 32 and flow control apertures 51, that can  
15 regulate the velocity, volume, pressure, and/or flowrate of the fluid drawn into the strainer 20 at a given point along the intake surface.

In the instance where the suction strainer 20 is disposed in a body of water, the intake velocity of the water entering the strainer bodies 21 can be regulated by the flow control mechanisms such that the water's intake velocity is low enough for aquatic animals to swim  
20 away from the surface of the strainer bodies 21, thus avoiding trapping the aquatic animals on the intake surfaces and possibly clogging the system. However, the suction strainers, strainer assemblies and flow control mechanisms set forth herein can be used in other combinations and applications where it is desired to control one or more characteristics of flow through a strainer

structure. Even though the distances vary between the suction inlet 40 and the different parts of the suction strainer 20, the flow control mechanisms provided in the strainer bodies 21 can provide for a uniform flow across the entire suction strainer 20 and/or across each individual strainer body 21. As used herein, the term "uniform flow" can encompass one or more of the pressure, velocity, and flowrate of a fluid passing through the parts of the suction strainer 20. U.S. Provisional Patent Application, Serial No. 60/428,851, filed on November 25, 2002, is hereby incorporated by reference in its entirety as if fully set forth herein.

As shown in Figs. 1-3, the suction strainer 20 includes a plurality of strainer assemblies or bodies 21 that are sequentially aligned to form a flow line leading to suction inlet 40. Each strainer body 21 generally has a plurality of holes formed therein through which fluid can be drawn from outside the strainer body 21 into the internal chamber defined by the strainer body 21 and through the flow line leading to the suction inlet 40 of the suction pump that is in flow communication with the suction strainer 20. The flow line leading to the suction inlet is made up of the internal chambers of each strainer body 21 and the disk gaps 26 that are disposed between the strainer bodies 21.

Each strainer body 21 generally includes a first flow control plate 30 and a second flow control plate 32 that are separated from each other by plate spacers 36 and rim 24. The rim 24 of each strainer body 21 may be solid or include a plurality of holes 25 through which fluid can pass into the internal chamber of the strainer body 21. The holes 25 can be either simply filtering holes that limit the amount of solids drawn into the strainer body 21 or flow control mechanisms that are sized and aligned so as to regulate the flow characteristics of the fluid being drawn into the strainer body 21.

Each first flow control plate 30 of the strainer bodies 21 generally has a primary opening 56 and a plurality of flow control apertures 51 formed therein. Likewise, each second flow control plates 32 of the strainer bodies 21 generally has a secondary opening 58 that is surrounded by flow control apertures 51. The flow control apertures 51 formed on the first control plates can be arranged in series 54, each of which includes a plurality of flow control apertures 51. These series 54 can extend radially from the primary opening across the surface of the first flow control plates 30. Each flow control aperture 51 in each series 54 has an area that is greater than the flow control apertures 51 that are closer to the primary opening 56. In other words, the area of the flow control apertures 51 in the series 54 increases distally from the primary opening 56. For example, first flow control aperture 50 is closer to primary opening 56 and has a smaller area than second flow control aperture 52. In an alternative embodiment, the size of each flow control aperture 51 can be the same as or smaller than other apertures that are proximal or closer to the primary opening 56. In this instance, the number of apertures can increase extending distally from the primary opening so that the aggregate or total area of the flow control apertures still increases distally from the primary opening. Furthermore, in a given area at any given distance from the center of the primary opening 56 the aggregate area of flow control apertures can be equal regardless of the direction from the primary opening 56. Since the negative pressure generated by the suction pump tends to decrease distally or farther from the primary opening 56, the distally increasing collective area of the flow control apertures 51 can provide for a uniform, or otherwise controlled, flow of fluid into the strainer body 21.

The second flow control plates 32 are disposed upstream of the first flow control plates 30 that are within the same strainer bodies 21. Each second flow control plate 32 includes a secondary opening 58 formed therein through which fluid enters the particular strainer body 21

from the upstream bodies or the end of the suction strainer 20. The series 60 of flow control apertures 51 are radially aligned around the secondary opening 58 in a similar fashion to the alignment of the series 54 of flow control apertures 51 on the first flow control plates 30.

As shown in Fig. 3, the total area of the flow control apertures 51 on first flow control plate 30a is greater than the total area of the flow control apertures 51 on first flow control plate 30b. Likewise, the total area of the flow control apertures 51 on second flow control plate 32a is greater than the collective area of the flow control apertures 51 on second flow control plate 32b. The flow control apertures 51 in strainer body 21a are larger than the apertures 51 in strainer body 21b because strainer body 21a is farther away from suction inlet 40. Therefore, in the embodiment shown in Fig. 3, the aggregate areas of flow control apertures 51 on the strainer bodies increase distally from the suction inlet 40. The increased flow control aperture areas can provide a uniform flow not only across an individual strainer body, but also across the entire span of the strainer assembly 20.

The screen plates 34 are disposed on the outside of each strainer body 21. The screen plates 34 are aligned to allow fluid to enter the strainer bodies 21, but limit the solids that enter the bodies 21. Each screen plate 34 is separated from the flow control surface of the adjacent flow control plate by disk spacers 38 and standoffs 31, which are formed on the flow control plates 30 and 32. The screen plates 34 can comprise perforated plates, wire, interwoven mesh or other suitable filter media. In applications wherein filtering is not an issue, the screen plates need not be included in the strainer bodies.

The suction strainer 20 is held together by tension rods 22, which are disposed in opening in every flow control plate, screen plate and end plate in the strainer 20. The tension rods 22 can also serve to support the strainer bodies 21 by connecting them to a support structure, such as the



end plate 28, which, in some embodiments, is a structural member designed to support the weight of all or a portion of the suction strainer 20. The tension rods 22 can be secured by welding or fasteners, such as nuts. In some embodiments, the size of the suction strainer 20 can be quite substantial thereby calling for support members, such as the tension rods 22, to be provided. In one particular embodiment, the suction strainer 20 has strainer bodies 21 that are approximately 10 to 12 feet in diameter for use in conjunction with the cooling system of a pressurized water reactor nuclear plant. With strainer bodies 21 of this size, tension rods 22 can contribute substantially to the overall support of the suction strainer 20.

The end plate 28 caps the end of the suction strainer 20 and can form a portion of the end suction strainer 21a. The end plate 28 can be solid, wire mesh, or a perforated plate, depending upon the application and the flow characteristics of the strainer 20.

The screens 34, rims 24, rods 22, end plates 28, first control plates 30, second control plates 32, gap disks 26 and the other portions of the suction strainer 20 can be formed of materials that will provide the appropriate durability in the conditions in which the strainer 20 is employed. For example, the parts of the suction strainer 20 may be formed of polymeric materials, such as polyvinyl chloride or chlorinated polyvinyl chloride, or metals, such as stainless steel, and can be coated with corrosion-resistant or other performance enhancing coatings that increase the working life and performance of the strainer 20 in the chosen environment.

In use, the suction strainer 20 is connected to the suction inlet 40 of a suction pump and partially or completely submerged in a fluid, such as water in a river, pond, or lake. The suction pump is activated, thereby creating a negative pressure or suction in the suction inlet 40 and the flow line and strainer bodies 21 of the suction strainer 20. Fluid is suctioned into the internal

chambers of each strainer body 21 through the screen plates 34 and the flow control apertures 51 on each flow control plate 30 and 32. The negative pressure or suction at each flow control aperture 51 varies with its distance from the suction inlet 40 and the primary opening 56 in the particular strainer body 21. The flow control apertures 51 are sized and aligned in each strainer  
5 body 21 so that the intake velocity of the fluid is generally uniform across the entire expanse of each strainer body 21. And where the aggregate area of the flow control apertures 51 increase in each strainer body 21 distally from the suction inlet 40, the fluid intake velocity generally is uniform across the entire extent of the suction strainer 20. The screen plates 34 prevent solids of  
10 a predetermined size from being suctioned with the fluid into the internal chambers of the strainer bodies 21. Fluid is suctioned into the internal chamber of a suction body 21 and then sucked through the primary opening 56 of the first flow control plate 30 and then through the downstream disk gaps 26. The fluid then travels in turn through the secondary openings 58 and the primary openings 56 of each downstream strainer body 21 until it reaches the suction inlet 40.

Although the strainer assembly 20 shown in Figs. 1-3 includes strainer bodies 21 that  
15 each include a first flow control plate 30 and a second flow control plate 32 separated by a rim 24 and enclosed by screen plates 34 and end plate 28, other configurations are contemplated and encompassed by the present invention. For example, instead of a rim and plate spacers connecting the two flow control plates, the flow control plates can be formed as concave portions of a shell that connect directly to each other and still define an internal chamber into which fluid  
20 can be drawn. In the embodiment shown in Fig. 3, each series 54 of flow control apertures extends radially away from the primary opening 56, which is shown as being centrally aligned in flow control plate 30. However, the flow control plates can have alternative configurations. For example, the primary opening can be offset from center. The flow control apertures can be more

randomly distributed across the flow control plate in such a way as to still provide increasing aperture area distally from the primary opening, such as by increasing the number of apertures moving away from the primary opening.

Also, in another embodiment, the screen plates can be formed directly on the flow control  
5 plates and extend across each of the flow control apertures. In other alternative embodiments, a core tube can be provided to extend through the interiors of each strainer body and connect the bodies to the suction inlet of the pump. The core tube can include intake holes formed along its length through which fluid is drawn from the interior of the strainer bodies. The core tube holes can be sized and aligned to provide flow control characteristics, such as by providing holes of  
10 increasing area moving distally from the suction inlet. These and other embodiments are encompassed by the present invention.

While certain embodiments of the present invention have been disclosed herein, other embodiments of the present invention will suggest themselves to persons skilled in the art in view of this disclosure. Therefore, it will be understood that variations and modifications can be  
15 effected within the spirit and scope of the invention and that the scope of the present invention should only be limited by the claims below. It is also understood that any relative relationships and dimensions shown on the drawings are given as example relative relationships and dimensions, but the scope of the invention is not to be limited thereby.